Product data sheet
Characteristics

AP7920B
APC NetShelter Switched Rack PDU, 1U, 1PH, 2.3kW 230V 10A or 2.5kW 208V 12A, 8 C13 outlets, C14 cord



Overview

Presentation	This APC Switched Rack PDU power distribution unit has a wide range of standardized PDU fe

Main

Product or component type	PDU
Main Input Voltage	200 V 208 V 230 V
Input current limits	15 A
Network frequency	50/60 Hz
Output voltage	208 V 230 V
Input Connection Type	IEC 60320 C14
Number of power socket outlets	8 IEC 60320 C13
Load capacity	2300 VA
[In] rated current	12 A
Permissible voltage	200…240 V
Max current draw	10 A
PDU type	Switched
Number of rack unit	1U
Number of cables	1
Cable length	1.9 M
Provided equipment	Installation guide Rack mounting brackets User manual

Complementary

Mounting location	Front Rear
Mounting mode	Rack-mounted
Mounting position	Horizontal
Height	44 Mm
Width	445 Mm
Depth	108 Mm
Net weight	2.27 Kg

Environmental

Product certifications	cUL listed[RETURN]CE[RETURN]CSA[RETURN]GOST[RETURN]IRAM[RETURN]UL listed[RETU
Standards	EN 55022 class A EN 55024 EN 61000-3-2 EN 61000-3-3 UL 60950
Relative humidity	0…95 %
Storage Relative Humidity	0…95 %
Ambient air temperature for storage	-25…65 °C
Storage altitude	0…15240 M
Operating altitude	0...10000 ft
Ambient air temperature for operation	0…45 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.000 Cm
Package 1 Width	49.000 Cm
Package 1 Length	34.500 Cm
Package 1 Weight	3.741 Kg
Unit Type of Package 2	P06
Number of Units in Package 2	17
Package 2 Height	76.000 Cm
Package 2 Width	60.000 Cm
Package 2 Length	80.000 Cm
Package 2 Weight	65.000 Kg

Offer Sustainability

Recyclability potential, in %	71
Total lifecycle Carbon footprint	1 221 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	19.1541506024
Carbon footprint of the manufacturing phase [A1 to A3]	19 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.0858468072
Carbon footprint of the distribution phase [A4]	0.1 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.5392391566
Carbon footprint of the installation phase [A5]	0.5 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	1199.9237649219
REACh free of SVHC	Yes
Carbon footprint of the use phase [B2, B3, B4, B6]	1 200 kg CO2 eq.
Mercury free	Yes
Sustainable packaging	No
Carbon footprint of the end-of-life phase [C1 to C4]	1.3202277108
Carbon footprint of the end-of-life phase [C1 to C4]	1 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Total lifecycle Carbon footprint	1221
Average percentage of recycled plastic content	15 %
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
SCIP Number	2cd1c284-4861-4713-bfcf-329f2772ce86
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant By Exemption
End of life manual availability	End Of Life Information
Removable battery	Yes

Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection a

Contractual warranty

Warranty (in months)	24

Product Life Status : Commercialised