Product data sheet
Characteristics

AP8704S-WW
Power Cord Kit (6 ea), Locking, C13 to C14, 1.2m



Overview

Presentation	This Series of Rack Power Distribution Units (PDU) comes with Locking IEC Receptacles. The

Main

Product or component type	Power cord
Input current limits	10 A
Input Connection Type	IEC 60320 C14
Max current draw	10 A
Max line current	10 A
Number of cables	6
Cable length	1.21 M
Power cable length	1.2 M

Complementary

Mounting preference	No preference
Mounting mode	Not rack-mountable
Height	240 Mm
Width	70 Mm
Depth	45 Mm
Net weight	1.01 Kg

Environmental

Product certifications	CCC[RETURN]PSE[RETURN]VDE
Relative humidity	20…80 %
Storage Relative Humidity	20…80 %
Ambient air temperature for storage	-25…75 °C
Storage altitude	0…15240 M
Operating altitude	0...10000 ft
Ambient air temperature for operation	0…70 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	24 Cm
Package 1 Width	4.5 Cm
Package 1 Length	7 Cm
Package 1 Weight	1.01 Kg

Offer Sustainability

Recyclability potential, in %	30
Total lifecycle Carbon footprint	134 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	4.703865480558076
Carbon footprint of the manufacturing phase [A1 to A3]	5 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.0762251199777845
Carbon footprint of the distribution phase [A4]	0.1 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.439916957135563
Carbon footprint of the installation phase [A5]	0.4 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	127.2878948439807
REACh free of SVHC	Yes
Carbon footprint of the use phase [B2, B3, B4, B6]	127 kg CO2 eq.
Lead free	Yes
Sustainable packaging	No
Carbon footprint of the end-of-life phase [C1 to C4]	1.77099827493267
Carbon footprint of the end-of-life phase [C1 to C4]	2 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Total lifecycle Carbon footprint	134
Average percentage of recycled plastic content	15 %
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
SCIP Number	1cdb2fed-a06f-4574-913d-8df8e70936b2
REACh Regulation	Free of Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant
Halogen-free status	Product contains halogen above thresholds
End of life manual availability	End Of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and

Contractual warranty

Warranty (in months)	24

Product Life Status : Commercialised