Product data sheet
Characteristics

AP8706S-WW
Power Cord Kit (6 ea), Locking, C13 to C14, 1.8m



Overview

Presentation	This Series of Rack Power Distribution Units (PDU) comes with Locking IEC Receptacles. The

Main

Product or component type	Power cord
Input current limits	10 A
Input Connection Type	IEC 60320 C14
Max current draw	10 A
Max line current	10 A
Number of cables	6
Cable length	1.82 Mm
Power cable length	1.8 M

Complementary

Mounting preference	No preference
Mounting mode	Not rack-mountable
Height	240 Mm
Width	75 Mm
Depth	55 Mm
Net weight	1.35 Kg

Environmental

Product certifications	CCC[RETURN]PSE[RETURN]VDE
Relative humidity	20…80 %
Storage Relative Humidity	20…80 %
Ambient air temperature for storage	-25…75 °C
Storage altitude	0…15240 M
Operating altitude	0...10000 ft
Ambient air temperature for operation	0…70 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	25.400 Cm
Package 1 Width	33.020 Cm
Package 1 Length	55.800 Cm
Package 1 Weight	1.210 Kg
Unit Type of Package 2	CAR
Number of Units in Package 2	10
Package 2 Height	26.000 Cm
Package 2 Width	33.000 Cm
Package 2 Length	56.000 Cm
Package 2 Weight	12.950 Kg

Offer Sustainability

Recyclability potential, in %	30
Total lifecycle Carbon footprint	179 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	6.287344949260796
Carbon footprint of the manufacturing phase [A1 to A3]	6 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.10188506135644464
Carbon footprint of the distribution phase [A4]	0.1 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.5880078139930793
Carbon footprint of the installation phase [A5]	0.6 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	170.13728518749895
REACh free of SVHC	Yes
Carbon footprint of the use phase [B2, B3, B4, B6]	170 kg CO2 eq.
Lead free	Yes
Sustainable packaging	No
Carbon footprint of the end-of-life phase [C1 to C4]	2.367175912038718
Carbon footprint of the end-of-life phase [C1 to C4]	2 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Total lifecycle Carbon footprint	179
Average percentage of recycled plastic content	15 %
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
SCIP Number	1cdb2fed-a06f-4574-913d-8df8e70936b2
REACh Regulation	Free of Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant
Halogen-free status	Product contains halogen above thresholds
End of life manual availability	End Of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and

Contractual warranty

Warranty (in months)	24

Product Life Status : Commercialised