Product data sheet
Characteristics

AP8760
Power Cord, Locking C19 to C20, 3.0m



Overview

Presentation	Free up space and secure power cords between rack-mount PDUs and attached IT equipment

Main

Product or component type	Power cord
Input Connection Type	IEC 60320 C20
Max current draw	16 A
Max line current	16 A
Number of cables	1
Cable length	3 M
Power cable length	3.05 M

Complementary

Mounting preference	No preference
Mounting mode	Not rack-mountable
Height	230 Mm
Width	230 Mm
Depth	45 Mm
Net weight	0.51 Kg

Environmental

Product certifications	CCC[RETURN]CSA[RETURN]PSE[RETURN]UL listed[RETURN]VDE
Relative humidity	20…80 %
Storage Relative Humidity	20…80 %
Ambient air temperature for storage	-25…75 °C
Storage altitude	0…15240 M
Operating altitude	0...10000 ft
Ambient air temperature for operation	0…75 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	23 Cm
Package 1 Width	23 Cm
Package 1 Length	4.5 Cm
Package 1 Weight	0.51 Kg

Offer Sustainability

Recyclability potential, in %	30
Total lifecycle Carbon footprint	59 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	2.3752192030540784
Carbon footprint of the manufacturing phase [A1 to A3]	2 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.03848991206799019
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.2221362852862744
Carbon footprint of the installation phase [A5]	0.2 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	55.7459766001859
REACh free of SVHC	Yes
Carbon footprint of the use phase [B2, B3, B4, B6]	56 kg CO2 eq.
Lead free	Yes
Sustainable packaging	No
Carbon footprint of the end-of-life phase [C1 to C4]	0.8942664556590711
Carbon footprint of the end-of-life phase [C1 to C4]	0.9 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Total lifecycle Carbon footprint	59
Average percentage of recycled plastic content	15 %
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
SCIP Number	1cdb2fed-a06f-4574-913d-8df8e70936b2
REACh Regulation	Free of Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant
Halogen-free status	Product contains halogen above thresholds
End of life manual availability	End Of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and

Contractual warranty

Warranty (in months)	24

Product Life Status : Commercialised