Product data sheet
Characteristics

AP8853X678
APC NetShelter Metered Rack PDU, 2G, 0U, 32A, 230V, Clipsal 56 series AS/NZ input plug, 36 C13 and 6 C19 outlets



Overview

Presentation	APC Metered Rack Power Distribution Units (PDUs) provide active metering to enable energy c

Main

Product or component type	PDU
Main Input Voltage	200 V 208 V 230 V
Input current limits	32 A
Network frequency	50/60 Hz
Output voltage	230 V
Number of power socket outlets	36 IEC 60320 C13 6 IEC 60320 C19
Permissible voltage	220…240 V
Max current draw	32 A
Max line current	32 A
PDU type	Metered
Protection type	Circuit breaker
Number of rack unit	0U
Number of cables	1
Cable length	2.9 M
Provided equipment	Installation guide Rack mounting brackets Serial configuration cable

Complementary

Mounting location	Side
Mounting mode	Rack-mounted
Mounting position	Vertical
Height	1791 Mm
Width	56 Mm
Depth	44 Mm
Net weight	6.93 Kg

Environmental

Product certifications	VDE
Relative humidity	5…95 %
Storage Relative Humidity	5…95 %
Ambient air temperature for storage	-25…65 °C
Storage altitude	0…15240 M
Operating altitude	0...10000 ft
Ambient air temperature for operation	-5…45 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	200 Cm
Package 1 Width	10.7 Cm
Package 1 Length	16.2 Cm
Package 1 Weight	8.56 Kg

Offer Sustainability

REACh free of SVHC	Yes
Lead free	Yes
Mercury free	Yes
Sustainable packaging	No
Environmental Disclosure	Product Environmental Profile
Average percentage of recycled plastic content	15 %
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
SCIP Number	1cdb2fed-a06f-4574-913d-8df8e70936b2
REACh Regulation	Free of Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant By Exemption
Halogen-free status	Product contains halogen above thresholds
End of life manual availability	End Of Life Information
Removable battery	Yes
Take-back	No

Contractual warranty

Warranty (in months)	24

Product Life Status : Commercialised