Product data sheet
Characteristics

AP9559
Rack PDU,Basic, 1U, 16A,208&230V, (10)C13 & (2)C19



Main

Product or component type	PDU
Main Input Voltage	120 V 208 V 230 V
Input current limits	16 A
Network frequency	50/60 Hz
Output voltage	120 V 208 V 230 V
Input Connection Type	IEC 60320 C20
Number of power socket outlets	10 IEC 60320 C13 2 IEC 60320 C19
Load capacity	3680 VA
Permissible voltage	90…250 V
Max current draw	16 A
Max line current	16 A
PDU type	Basic
Protection type	Without circuit breaker
Number of rack unit	1U
Number of cables	1
Cable length	2.49 M
Provided equipment	User manual Rack mounting brackets

Complementary

Mounting location	Front Rear
Mounting mode	Rack-mounted
Mounting position	Horizontal
Height	44 Mm
Width	447 Mm
Depth	57 Mm
Net weight	0.98 Kg

Environmental

Product certifications	cUL listed[RETURN]CE[RETURN]UL listed[RETURN]VDE[RETURN]Victoria
Relative humidity	0…95 %
Storage Relative Humidity	0…95 %
Ambient air temperature for storage	-25…65 °C
Storage altitude	0…15240 M
Operating altitude	0...10000 ft
Ambient air temperature for operation	0…45 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	16.5 Cm
Package 1 Width	48.3 Cm
Package 1 Length	15.2 Cm
Package 1 Weight	2.355 Kg

Offer Sustainability

Recyclability potential, in %	45
Total lifecycle Carbon footprint	2 394 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	0.1700731761
Carbon footprint of the manufacturing phase [A1 to A3]	0.2 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.1700731761
Carbon footprint of the distribution phase [A4]	0.2 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	2384.9323857868
REACh free of SVHC	Yes
Carbon footprint of the use phase [B2, B3, B4, B6]	2 385 kg CO2 eq.
Lead free	Yes
Sustainable packaging	No
Carbon footprint of the end-of-life phase [C1 to C4]	0.1498533321
Carbon footprint of the end-of-life phase [C1 to C4]	0.1 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Total lifecycle Carbon footprint	2394
Average percentage of recycled plastic content	15 %
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
SCIP Number	1cdb2fed-a06f-4574-913d-8df8e70936b2
REACh Regulation	Free of Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant
Halogen-free status	Product contains halogen above thresholds
End of life manual availability	End Of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and

Contractual warranty

Warranty (in months)	24

Product Life Status : Commercialised