Product data sheet
Characteristics

AP9565
APC NetShelter Basic Rack PDU, 1U, 1PH, 3.7kW 230V 16A or 3.3kW 208V 16A, x12 C13 outlets, C20 cord



Overview

Presentation	Reliable rack power distribution designed to increase manageability and efficiency in the data c

Main

Product or component type	PDU
Main Input Voltage	200 V 208 V 230 V
Input current limits	16 A
Network frequency	50/60 Hz
Output voltage	208 V 230 V
Input Connection Type	IEC 60320 C20
Number of power socket outlets	12 IEC 60320 C13
Load capacity	3680 VA
Max current draw	16 A
PDU type	Basic
Number of rack unit	1U
Number of cables	1
Cable length	2.49 M
Provided equipment	Installation guide Rack mounting brackets

Complementary

Mounting location	Front Rear
Mounting mode	Rack-mounted
Mounting position	Horizontal
Height	44 Mm
Width	447 Mm
Depth	57 Mm
Net weight	2.05 Kg

Environmental

Product certifications	cUL listed[RETURN]CE[RETURN]Queensland Australia[RETURN]UL listed[RETURN]VDE
Standards	UL 60950
Relative humidity	0…95 %
Storage Relative Humidity	0…95 %
Ambient air temperature for storage	-25…65 °C
Storage altitude	0…15240 M
Operating altitude	0...10000 ft
Ambient air temperature for operation	0…45 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7 Cm
Package 1 Width	46.4 Cm
Package 1 Length	22.9 Cm
Package 1 Weight	3.632 Kg

Offer Sustainability

Recyclability potential, in %	45
Total lifecycle Carbon footprint	2 398 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	0.2615956056
Carbon footprint of the manufacturing phase [A1 to A3]	0.3 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.2615956056
Carbon footprint of the distribution phase [A4]	0.3 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	2384.9323857868
REACh free of SVHC	Yes
Carbon footprint of the use phase [B2, B3, B4, B6]	2 385 kg CO2 eq.
Lead free	Yes
Sustainable packaging	No
Carbon footprint of the end-of-life phase [C1 to C4]	0.2304947438
Carbon footprint of the end-of-life phase [C1 to C4]	0.2 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Total lifecycle Carbon footprint	2398
Average percentage of recycled plastic content	15 %
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
SCIP Number	1cdb2fed-a06f-4574-913d-8df8e70936b2
REACh Regulation	Free of Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant
Halogen-free status	Product contains halogen above thresholds
End of life manual availability	End Of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and

Contractual warranty

Warranty (in months)	24

Product Life Status : Commercialised