Product data sheet
Characteristics

AP9568
Rack PDU, Basic, Zero U, 10A,230V, (15)C13



Main

Product or component type	PDU
Main Input Voltage	120 V 200 V 208 V 230 V 240 V
Input current limits	10 A
Network frequency	50/60 Hz
Output voltage	208 V 230 V
Input Connection Type	IEC 60320 C14
Number of power socket outlets	15 IEC 60320 C13
Load capacity	2300 VA
Permissible voltage	100…240 V
Max current draw	10 A
PDU type	Basic
Number of rack unit	0U
Number of cables	1
Cable length	1.98 M
Provided equipment	Installation guide Rack mounting brackets Toolless mounting kit

Complementary

Mounting location	Side
Mounting mode	Rack-mounted
Mounting position	Vertical
Height	610 Mm
Width	44 Mm
Depth	44 Mm
Net weight	2 Kg

Environmental

Product certifications	cUL listed[RETURN]CE[RETURN]GOST[RETURN]Queensland Australia[RETURN]UL listed[RETU
Relative humidity	0…95 %
Storage Relative Humidity	0…95 %
Ambient air temperature for storage	-25…65 °C
Storage altitude	0…15240 M
Operating altitude	0...10000 ft
Ambient air temperature for operation	0…45 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	64.8 Cm
Package 1 Width	17.8 Cm
Package 1 Length	15.2 Cm
Package 1 Weight	2.724 Kg

Offer Sustainability

Recyclability potential, in %	45
Total lifecycle Carbon footprint	942 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	0.196016542
Carbon footprint of the manufacturing phase [A1 to A3]	0.2 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.196016542
Carbon footprint of the distribution phase [A4]	0.2 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	931.614213198
REACh free of SVHC	Yes
Carbon footprint of the use phase [B2, B3, B4, B6]	932 kg CO2 eq.
Lead free	Yes
Sustainable packaging	No
Carbon footprint of the end-of-life phase [C1 to C4]	0.1727123149
Carbon footprint of the end-of-life phase [C1 to C4]	0.2 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Total lifecycle Carbon footprint	942
Average percentage of recycled plastic content	15 %
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
SCIP Number	1cdb2fed-a06f-4574-913d-8df8e70936b2
REACh Regulation	Free of Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant
Halogen-free status	Product contains halogen above thresholds
End of life manual availability	End Of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and

Contractual warranty

Warranty (in months)	24

Product Life Status : Commercialised