Product data sheet
Characteristics

APDU11350ME
APC NetShelter Rack PDU Advanced Gen 2, Metered, 3Phase, 22.1kW 400V 32A or 17.3kW 415V 30A, 530P6, 48 Outlet



Main

Product or component type	PDU
Main Input Voltage	415 V 3 phases 400 V 3 phases
Input current limits	30 A
Network frequency	50/60 Hz
Output voltage	240 V
Input Connection Type	IEC 60309 30 A 3P + N + PE
Number of power socket outlets	24 C13/C15/C19/C21 24C13/C15
Load capacity	17300 VA
[In] rated current	24 A
Permissible voltage	200…240 V 346…415 V
Max current draw	24 A
PDU type	Metered
Protection type	Circuit breaker
Number of rack unit	0U
Cable length	3 M

Complementary

Mounting location	Side
Mounting mode	Rack-mounted
Mounting position	Vertical
Communication port protocol	1000BASE-T 10/100BASE-T
Height	1780 Mm
Width	56 Mm
Depth	75 Mm
Net weight	8.4 Kg

Environmental

Standards	UL 62368-1 CSA C22.2 No 62368-1 FCC part 15 Subpart B CE EN 62368-1
IP degree of protection	IP44
Relative humidity	5…95 %
Storage Relative Humidity	5…95 %
Ambient air temperature for storage	-25…65 °C
Storage altitude	0…15240 M
Operating altitude	0...10000 ft
Ambient air temperature for operation	-5…60 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	198 Cm
Package 1 Width	13.2 Cm
Package 1 Length	26.2 Cm
Package 1 Weight	11.4 Kg

Offer Sustainability

Mercury free	Yes
Sustainable packaging	No
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	31346aed-552c-4a16-81d9-e683a383b6da
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant By Exemption
Removable battery	No
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and

Contractual warranty

Warranty (in months)	36

Product Life Status : Commercialised