Product data sheet
Characteristics

AR3140
APC NetShelter SX, Networking Rack Enclosure, 42U, Black, 1991H x 750W x 1070D mm with Casters, Feet, Vertical Cable Managers, Side Panels



Overview

Presentation	NetShelter SX Networking Enclosure expands Schneider Electric's superior IT enclosure line w

Main

Product or component type	Rack enclosure
Number of rack unit	42U
Rack width	19"
Permanent permissible load	1020.6 Kg dynamic 1701.0 Kg static
Provided equipment	Baying hardware Key(S) Keyed-alike doors and side panels Leveling feet Mounting hardware Pre-installed casters Side panels Vertical cable managers

Complementary

Mounting mode	Not rack-mountable
Minimum mounting depth	279.4 Mm
Maximum mounting depth	819.2 Mm
Colour	Black
Marking	14 gauge EIA mounting rail 16 gauge front door 16 gauge post 16 gauge rear door 18 gauge roof 18 gauge side panels
Height	1991 Mm
Width	750 Mm
Depth	1070 Mm
Net weight	155.95 Kg

Environmental

Standards	UL 2416 UL 60950-1 EIA-310E

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	211.8 Cm
Package 1 Width	85.09 Cm
Package 1 Length	115.6 Cm
Package 1 Weight	168.18 Kg

Offer Sustainability

Recyclability potential, in %	95
Total lifecycle Carbon footprint	590 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	563.3337596930211
Carbon footprint of the manufacturing phase [A1 to A3]	563 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	14.25140298984731
Carbon footprint of the distribution phase [A4]	14 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0
REACh free of SVHC	Yes
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Sustainable packaging	No
Carbon footprint of the end-of-life phase [C1 to C4]	12.530478855224239
Carbon footprint of the end-of-life phase [C1 to C4]	13 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Total lifecycle Carbon footprint	590
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
REACh Regulation	Free of Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant
End of life manual availability	No need of specific recycling operations
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and

Contractual warranty

Warranty (in months)	60

Product Life Status : Commercialised