Product data sheet
Characteristics

EPDU2132S
Easy PDU Switched Zero U 32A 230V(20)C13 (4)C19 IEC309



Main

Product or component type	PDU
Main Input Voltage	230 V 1 phase
Input current limits	32 A
Network frequency	50/60 Hz
Output voltage	230 V
Input Connection Type	IEC 60309 32 A 2P + E
Number of power socket outlets	20 IEC 60320 C13
Load capacity	7360 VA
Max current draw	32 A
PDU type	Switched
Number of rack unit	0U
Number of cables	1
Cable length	2.99 M
Provided equipment	Installation guide

Complementary

Mounting location	Side
Mounting mode	Rack-mounted
Mounting position	Vertical
Height	1650 Mm
Width	56 Mm
Depth	62 Mm
Net weight	6.65 Kg

Environmental

Product certifications	CE[RETURN]UKCA
Relative humidity	5…95 %
Storage Relative Humidity	5…95 %
Ambient air temperature for storage	-25…65 °C
Operating altitude	0...10000 ft
Ambient air temperature for operation	-5…50 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12.6 Cm
Package 1 Width	17 Cm
Package 1 Length	181 Cm
Package 1 Weight	8.15 Kg

Offer Sustainability

Recyclability potential, in %	44
Total lifecycle Carbon footprint	1 310 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	89.58350535987881
Carbon footprint of the manufacturing phase [A1 to A3]	90 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	16.151780290906743
Carbon footprint of the distribution phase [A4]	16 kg CO2 eq.
Carbon footprint of the installation phase [A5]	4.546463761815773
Carbon footprint of the installation phase [A5]	5 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	1186.8680993637145
Carbon footprint of the use phase [B2, B3, B4, B6]	1 187 kg CO2 eq.
Mercury free	Yes
Sustainable packaging	No
Carbon footprint of the end-of-life phase [C1 to C4]	13.184590749980721
Carbon footprint of the end-of-life phase [C1 to C4]	13 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Total lifecycle Carbon footprint	1310
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	C14fd57b-77a5-4296-8613-2f036f40e26e
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant By Exemption
End of life manual availability	End Of Life Information
Removable battery	No
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and

Contractual warranty

Warranty (in months)	24

Product Life Status : Commercialised