

# JVS-H410D

4MP Wi-Fi Two-Way Talk Pan/Tilt IP camera



## Features

- 4MP Ultra-clear Image Quality;
- Built-in Speaker + MIC;
- Support Wi-Fi Connection, Wired Connection and AP Connection;
- Built-in Bluetooth Module, Support Bluetooth Network Configuration;
- Support Humanoid Detection;
- Support SD Card, Maximum Support 256G;

## Specifications

Video	
Image Sensor	1/3" CMOS Sensor
Max Resolution	2560x1440
Effective Pixels	4.0MP
Compression Standard	H.264/H.265(Default)
Frame Rate	20fps
Bitrate	Main Stream: 128Kbps ~ 4096Kbps Sub Stream: 68Kbps~1024Kbps
SNR (dB)	50dB
Min. Illumination	0.01Lux (light ON)
Lens	

<b>Interface Type</b>	M12
<b>Lens</b>	2.8mm
<b>FOV</b>	H: 83°, V: 42°, D: 108°
<b>Function</b>	
<b>Audio Codec</b>	G.711U/G.711A (Default)
<b>Exposure Control</b>	Auto
<b>White Balance</b>	Auto
<b>Gain Control</b>	Auto
<b>Digital 3D Noise Reduction</b>	Support
<b>OSD Information Setting</b>	Large Font OSD, OSD Flashing on Alarm, OSD Position Settings
<b>SNTP</b>	Support
<b>Schedule Reboot</b>	Support
<b>Smart Defog</b>	Support
<b>Motion Detection</b>	Support Humanoid Detection
<b>Image Setting</b>	Support Saturation, Brightness, Contrast, Sharpness Adjustment
<b>Image Style</b>	Standard, Soft, Transparent
<b>Day and Night Function</b>	Automatic Switching, Timing Switching, Day Mode, Night Mode
<b>Privacy Mask</b>	Support Up To 8 Masking Areas
<b>Night Vision Optimization</b>	Support
<b>DWDR</b>	Support
<b>Screen Settings</b>	Screen Mirroring, Screen Flipping
<b>IP Adaptation</b>	Support Automatic Adaptation of IP Address
<b>Intelligent Analysis</b>	Not support
<b>Alarm Method</b>	Email Alarm, Client Alarm
<b>Remote Operation</b>	System, Audio and Video, Image, Alarm, Network management, Storage management, Intelligent Analysis
<b>Audio Function</b>	Built-in Mic and Speaker
<b>Storage</b>	Support SD Card (256G) ,Cloud Storage
<b>Reset Button</b>	Support
<b>Network</b>	
<b>Ethernet</b>	10/100Mbps Ethernet
<b>Wi-Fi</b>	2.4G Hz
<b>Bluetooth Network Configuration</b>	Support
<b>Stream</b>	2x Streams
<b>Network Protocols</b>	HTTP, TCP/IP, UDP, ICMP, RTSP, RTP, RTCP, SMTP, DHCP, DNS
<b>ONVIF</b>	Standard ONVIF
<b>Network Transmission</b>	CloudSEE 3.0
<b>Browser</b>	IE8+, Chrome18+, Firefox5.0+, Safari5.02+
<b>User</b>	Up to 13 Users
<b>App</b>	Support iOS/Android
<b>General</b>	
<b>Lights</b>	2 White LEDs + 2 IR LEDs
<b>Fill Light Distance</b>	IR LED:15 Meters
<b>Waterproof Level</b>	IP53
<b>Power Supply</b>	DC 5V
<b>Power Consumption</b>	<6W (During Day); <10W (At Night)
<b>Working Temperature</b>	-20°C ~ 60°C
<b>Working Humidity</b>	10% ~ 90% Rh
<b>Color/Material</b>	Black and white /PC+ABS
<b>Weight</b>	188g
<b>Installation Method</b>	Wall, Ceiling, Desktop

## Dimension:

