

JVS-N98-4G

3.0MP 4G Pan/Tilt Camera (ColorNext Series)



Features

- 3.0 Megapixel 2304x1296 Resolution.
- Support 4G SIM Card
- External Dual 4G High-gain Antennas
- 12x Warm LEDs + 6x IR LEDs
- Blue & Red Warning Lights
- Built-in Mic and Speaker
- Support Human Tracking
- Support SD Card Max. 512GB
- Ingress Protection IP67

Specifications

CAMERA	
Image Sensor	1/2.9" Progressive CMOS
Min. Illumination	LEDs ON 0 Lux
Day & Night	IR Cut filter with auto switch
Lens	3.6mm/6mm
Viewing Angle	3.6mm H: 82.4°, V: 44.0°, D: 95.9° 6mm H: 53.3°, V: 29.2°, D: 60.4°
Rotation Angle	Pan: -170° ~ 170°; Tilt: -9° ~ 110°
LEDs	12x Warm LEDs + 6x IR LEDs
LED Range	IR LED up to 40m, Warm LED up to 30m
Alarm	Blue & Red Warning Lights
IMAGE	
Max Resolution	2304x1296
Frame Rate	20fps
Video Compression	H.265/H.264
Bit Rate (CBR/VBR)	Main Stream: 128-4096Kbps. Default 2380Kbps Sub Stream: 68-1024Kbps. Default 256Kbps
Audio Compression	G.711a / G.711u
Image Setting	Saturation, Brightness, Contrast, Sharpness
Image Enhancement	BLC/HLC/3D DNR/Defog
White Balance	Auto
Privacy Mask	Support 8 Rectangle Areas
DWDR	Support
NETWORK	
Network Protocols	HTTP, TCP/IP, UDP/IP, ICMP, RTP, UDP, RTCP, SMTP, DHCP, DNS
Interface Protocols	Standard ONVIF, GB28181, CloudSEE
Auto IP Configuration	Support
Alarm Trigger	Motion Detection, Region Intrusion, Line Crossing, Humanoid Detection, Video Occlusion
RTSP Video	Standard RFC2326, QuickTime/VLC Player etc.
Security	User security authentication, Reset, Hardware Watch Dog
Web Language	Chinese, English
Browser	IE8+, Chrome18+, Firefox5.0+, Safari5.02+
INTERFACE	
Ethernet	1 RJ45 10M / 100M Ethernet
4G	LTE-TDD: B34/B38/B39/B40/B41 LTE-FDD: B1/B3/B5/B8
Audio	Built-in Mic and Speaker
SD Card	Support Max. 512GB
Reset Button	Support
GENERAL	
Power Supply	DC12V/2A
Power Consumption	<9W (During Day); <12W (At Night)
Working Temperature	-20°C ~ 60°C
Working Humidity	10% ~ 90% Rh Non-Condensation
Dimensions	160×303.5×182(mm)
Product Weight	≤746g
Installation	Wall, Ceiling, Pole