


RG-RAP1261

Reyee Wi-Fi 6 AX3000 Ultra-Thin Wall Plate Access Point




Highlights

- Dual-radio performance, gigabit wireless wall-mounted AP
- Better experience with Cooling Patent Technology
- Easy installation, 86mm standard compatible
- Capable of Reyee Mesh and 802.11K/V/R
- Powerful Standalone Portal via Ruijie Cloud

Highlight Features

AX3000 Dual-Band Ultra-Thin Wall Plate Access Point

RG-RAP1261



Experience Wi-Fi 6, Experience Gigabit Internet

New upgrade to AX3000, Speed Test reaches 950Mbps, delivering the fastest possible internet experience




Easy Installation, Worldwide Compatible



Highlight Features

Unprecedented This Design with 8.5mm and Patent Technology

Thinner, Cooler, Stronger. Averagely reduced 7.c in working mode




Smart AI Roaming Enhances Wireless Experience Anywhere You Go



Cloud, Make Your Business Easy

- Self-organizing network
- Cloud portal authentication
- Remote monitoring and maintenance
- Upgrade firmware via Cloud
- APP library dynamically update



Product Information

Model	RG-RAP1261
Product Type	Wall AP

Hardware Specifications

Model	RG-RAP1261
Wi-Fi Radio	
6 GHz Wi-Fi	No
5 GHz Wi-Fi	Wi-Fi 4 (IEEE 802.11a/n)
	Wi-Fi 5 (IEEE 802.11ac)
	Wi-Fi 6 (IEEE 802.11ax)
2.4 GHz Wi-Fi	Wi-Fi 4 (IEEE 802.11b/g/n)
	Wi-Fi 6 (IEEE 802.11ax)
Operating band	IEEE 802.11b/g/n/ax, 2.400 GHz to 2.4835 GHz IEEE 802.11a/n/ac/ax, 5.150 GHz to 5.350 GHz, 5.470 GHz to 5.725 GHz, 5.725 GHz to 5.850 GHz Note: Available bands vary with countries and regions. To use the preceding frequency bands, ensure that your country or region supports these frequency bands.
Radio design	Dual-radio
	4 spatial streams

Hardware Specifications

Model	RG-RAP1261
	<ul style="list-style-type: none">• 2.4 GHz: 2 x 2, MU-MIMO• 5 GHz: 2 x 2, MU-MIMO
FEM	iFEM
6 GHz channel width	No
5 GHz channel width	Auto/20/40/80/160 MHz
2.4 GHz channel width	Auto/20/40 MHz
Maximum wireless data rate	2974 Mbps
6 GHz wireless data rate	No
5 GHz wireless data rate	2401 Mbps
2.4 GHz wireless data rate	573 Mbps
Maximum transmit power	<p>Frequency bands and maximum Effective Isotropic Radiated Power (EIRP):</p> <p>Note: Country specific restrictions apply.</p> <p>European Union & United Kingdom:</p> <p>2400–2483.5 MHz, EIRP $\leq$ 20 dBm</p> <p>5150–5350 MHz, EIRP $\leq$ 23 dBm</p> <p>5470–5725 MHz, EIRP $\leq$ 30 dBm</p> <p>United States:</p> <p>2400–2483.5 MHz, max output power $\leq$ 30 dBm & EIRP $\leq$ 36 dBm</p> <p>5150–5250 MHz, max output power $\leq$ 30 dBm & EIRP $\leq$ 36</p>

/ Hardware Specifications

Model	RG-RAP1261
	dBm
	5250–5350 MHz, max output power < 24 dBm & EIRP ≤ 30
	dBm
	5470–5725 MHz, max output power < 24 dBm & EIRP ≤ 30
	dBm
	5725–5850 MHz, max output power ≤ 30 dBm & EIRP ≤ 36
	dBm
	Myanmar:
	2400–2483.5 MHz, EIRP ≤ 23 dBm
	5725–5825 MHz, EIRP ≤ 30 dBm
	Thailand:
	2400–2483.5 MHz, EIRP ≤ 20 dBm
	5150–5350 MHz, EIRP ≤ 23 dBm
	5470–5725 MHz, EIRP ≤ 30 dBm
	5725–5825 MHz, EIRP ≤ 30 dBm
	Indonesia:
	2400–2483.5 MHz, EIRP ≤ 27 dBm
	5150–5350 MHz, EIRP ≤ 23 dBm
	5725–5825 MHz, EIRP ≤ 23 dBm
	Egypt:
	2400–2483.5 MHz, EIRP ≤ 20 dBm
	5150–5350 MHz, EIRP ≤ 23 dBm

/ Hardware Specifications

Model	RG-RAP1261
	<p>Vietnam:</p> <p>2400–2483.5 MHz, EIRP $\leq$ 23 dBm</p> <p>5150–5350 MHz, EIRP $\leq$ 23 dBm</p> <p>5470–5725 MHz, EIRP $\leq$ 30 dBm</p> <p>5725–5850 MHz, EIRP $\leq$ 30 dBm</p>
Maximum transmit power (6 GHz)	No
Maximum transmit power (5 GHz)	<p>Combined power: 21 dBm (single-stream power: 18 dBm)</p> <p>Note: The transmit power varies according to regulations in different countries and regions.</p>
Maximum transmit power (2.4 GHz)	<p>Combined power: 21 dBm (single-stream power: 18 dBm)</p> <p>Note: The transmit power varies according to regulations in different countries and regions.</p>
Coverage range	<p>45 m² (484.38 square ft.)</p> <p>Note: The data is obtained in an ideal environment without obstruction. The signal coverage radius depends on client performance and environmental interference.</p>
Modulation	<p>OFDM: BPSK @ 6/9 Mbps, QPSK @ 12/18 Mbps, 16-QAM @ 24 Mbps, 64-QAM @ 48/54 Mbps</p> <p>DSSS: DBPSK @ 1 Mbps, DQPSK @ 2 Mbps, and CCK @ 5.5/11 Mbps</p> <p>MIMO-OFDM: BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM and</p>

Hardware Specifications

Model	RG-RAP1261
	1024-QAM
	OFDMA
Receive sensitivity	11b: -91 dBm (1 Mbps), -88 dBm (5.5 Mbps), -85 dBm (11 Mbps)
	11a/g: -89 dBm (6 Mbps), -80 dBm (24 Mbps), -76 dBm (36 Mbps), -71 dBm (54 Mbps)
	11n: -83 dBm (MCS0), -65 dBm (MCS7), -83 dBm (MCS8), -65 dBm (MCS15)
	11ac: 20 MHz: -83 dBm (MCS0), -57 dBm (MCS9)
	11ac: 40 MHz: -79 dBm (MCS0), -57 dBm (MCS9)
	11ac: 80 MHz: -76 dBm (MCS0), -51 dBm (MCS9)
	11ac: 160 MHz: -76 dBm (MCS0), -50 dBm (MCS9)
	11ax: 20 MHz: -85 dBm (MCS0), -58 dBm (MCS11)
	11ax: 40 MHz: -82 dBm (MCS0), -54 dBm (MCS11)
	11ax: 80 MHz: -79 dBm (MCS0), -52 dBm (MCS11)
	11ax: 160 MHz: -76 dBm (MCS0), -49 dBm (MCS11)
Dimensions and Weight	
Product dimensions (W x D x H)	86 mm x 42.4 mm x 86 mm (3.39 in. x 1.67 in. x 3.39 in.)
Color	White
Weight	≤ 0.16 kg (0.35 lbs.) (without packaging materials)
Shipping weight	≤ 0.19 kg (0.42 lbs.)

Hardware Specifications

Model	RG-RAP1261
Certification and Regulatory Compliance	
RoHS	Yes
Safety compliance	EN 62368-1
EMC	EN 55032
	EN 55035
	EN 61000-3-3
	EN 61000-3-2
	EN 301489-1
	EN 301489-3
RF	EN 301489-17
	EN 300 328
	EN 301 893
Certification	EN 300 440
	CE, CB
System Specifications	
Flash memory	128 MB
RAM	256 MB DDR3
Port Specifications	
Number of 10/100/1000BASE-T ports	2
Reset button	1
LEDs	1 x system status LED

Hardware Specifications

Model	RG-RAP1261
Antenna	
Antenna	Integrated 2.4 GHz and 5 GHz: 2 built-in omnidirectional antennas
Antenna horizontal orientation	No
Antenna vertical orientation	No
Antenna gain (6 GHz)	No
Antenna gain (5 GHz)	3.00 dBi
Antenna gain (2.4 GHz)	3.00 dBi
Environment and Reliability	
Operating temperature	0°C to 40°C (32°F to 104°F)
Storage temperature	−40°C to +70°C (−40°F to +158°F)
Operating humidity	5% RH to 95% RH (non-condensing)
Storage humidity	5% RH to 95% RH (non-condensing)
Mounting options	Junction box
IP rating	No
Surge protection	Ethernet port: ±2 kV for common mode
MTBF	400,000 hours
Power Supply and Consumption	
Power supply	PoE/PoE+
Local power supply	No
Dimensions of the DC connector	No

Hardware Specifications

Model	RG-RAP1261
PoE In standard	<ul style="list-style-type: none">• IEEE 802.3af (PoE)• IEEE 802.3at (PoE+)
PoE budget	No
Maximum power consumption	10.2 W

Software Specifications

Model	RG-RAP1261
Ethernet Interface	
PPPoE clients	Yes
Ethernet Switching	
IEEE 802.1Q VLAN	Yes
VLAN expansion	Yes
Enabling/Disabling an interface	Yes
Interface rate	10/100/1000 Mbps auto-negotiation
Interface mode (half-duplex/full-duplex switching)	Yes
WLAN	
Maximum number of associated wireless clients	64 (2.4 GHz)
	256 (5 GHz)
	256 (2.4 GHz and 5 GHz enabled)
Recommended number of associated wireless clients	● Support for IEEE 802.11ax and 160 MHz:
	16 (2.4 GHz)
	94 (5 GHz)
	110 (2.4 GHz and 5 GHz enabled)
	● Support for IEEE 802.11ax and 80 MHz:
	16 (2.4 GHz)
	64 (5 GHz)
	80 (2.4 GHz and 5 GHz enabled)

Software Specifications

Model	RG-RAP1261
	<ul style="list-style-type: none">● Support for IEEE 802.11ac:<ul style="list-style-type: none">8 (2.4 GHz)32 (5 GHz)40 (2.4 GHz and 5 GHz enabled)
Maximum number of SSIDs	8
Radio-based client limiting	Yes
Layer 2 isolation	Yes
OFDMA	Yes
WMM	Yes
DFS	Yes
MLO	No
4K-QAM	No
Different SSIDs for the same VLAN	Yes
Enabling/Disabling MLO	No
AP load balancing	Yes
Beamforming	Yes
802.11k/v roaming	Yes
Fast transition (802.11r)	Yes
Layer 2 roaming	Yes
Layer 3 roaming	Yes
AI roaming	Yes

Software Specifications

Model	RG-RAP1261
Co-channel roaming	Yes
Roaming sniffing	No
Configurable antenna	No
PSK authentication	Yes
Static allowlist	Yes
Adjusting the transmit power for beacon and probe frames	Yes
Encryption mode (WPA-PSK, WPA2-PSK, WPA/WPA2-PSK)	Yes
OWE (Enhanced Open) WPA3-SAE WPA2-PSK/WPA3-SAE	Yes
Number of blocklists and allowlists based on MAC addresses (single SSID)	256
Number of global blocklists/allowlists	256
Mesh management	Yes
AP Mesh	Yes
AP portal authentication	Yes

Software Specifications

Model	RG-RAP1261
Maximum number of devices that can be managed	300
One-Click Network Optimization	Yes
Static blocklist	Yes
Interface	
IPTV transparent transmission	Yes
Authentication	
802.1X authentication	Yes
Dynamic VLAN assignment	Yes
IPv4 Ruijie RG-OCE Identity Manager authentication scheme	Yes
Linkufi authentication	Yes
Multicast	
IGMP snooping (wireless-to-wireless)	Yes
IGMP snooping (wired-to-wireless)	Yes
IGMP snooping (wired-to-wired)	No
Basic Configurations	
AP mode	Yes
Routing mode	Yes
Internet access mode	Static IP address
	Static IPv6 address

Software Specifications

Model	RG-RAP1261
	Dynamic IP address
	Dynamic IPv6 address
	PPPoE
IP Service	
ARP binding	Yes
IPv4 ping	Yes
IPv6 ping	Yes
Traceroute	Yes
Static/Dynamic NAT	Yes
DHCP server	Yes
IPv6	Yes
Network Management and Monitoring	
Wireless repeater mode	Yes
Web login information	Single-device login address: 10.44.77.254 Network-wide login address: 10.44.77.253 Default password: admin
Network-wide configuration and management	Yes
Ruijie Reyee App management	Yes
eWeb management	Yes
Ruijie Cloud management	Yes

Software Specifications

Model	RG-RAP1261
SNMP	Yes
Configuration synchronization among the app, eWeb, and Ruijie Cloud	Yes
Displaying device information on Ruijie Cloud	Yes

Package Contents

Model	RG-RAP1261
Accessories	
Power adapter	No
Package Contents	
Package Contents	1 x AP
	2 x Cross pan head screws (M4 x 40 mm)
	1 x User Manual
	1 x Warranty Card

Ruijie | ReYee

 **R**edefine **y**our **e**asy network



Ruijie Networks Co., Ltd.

Official Website: <https://Reyee.Ruijie.com>