

RG-RAP2260(H)

Reyee Wi-Fi 6 AX6000 High-density Multi-G Ceiling Access Point



Highlights

- Build ultra-fast and high-density Wi-Fi with 5.95Gbps throughput.
- Client connections over 500, higher practical performance as well.
- Boost Internet speed with 5Gbps uplink for the future.
- Easily install extra AP with Reyee Mesh technology.
- Support standalone captive portal, easy to enable Wi-Fi authentication.

Highlight Features

Build Ultra-fast Wi-Fi Network for the Future

Interface

Installation



 AX6000
Wi-Fi 6

 4 x 4
MU-MIMO

 Dual 2.5GE
Wired Uplink

 Reyee Mesh
Technology

 Free Cloud
Management

Build Ultra-fast Wi-Fi Network for the Future

Interface

Installation



 AX6000
Wi-Fi 6

 4 x 4
MU-MIMO

 Dual 2.5GE
Wired Uplink

 Reyee Mesh
Technology

 Free Cloud
Management

Better Multi-User Experience in High-Density Scenarios

Performance upgraded, support client connections over 500.



Highlight Features


Boost Your Internet Speed with 5Gbps Uplink

Can be integrated dual 2.5GE uplink, build network for future.

Wireless 5952 Mbps

Wired 5000 Mbps

5Gbps



Easily Install Extra AP with Reyee Mesh


Less wiring, more relaxing.



Highlight Features


More Flexiable Wi-Fi Authentication

Support standalone captive portal, easy to enable Wi-Fi authentication based on Ruijie Cloud only.*



Cloud, Make Your Business Easy

- Self-organizing network
- Centralized network management
- Scenario based configuration
- Cloud portal authentication
- Remote monitoring and maintenance



/ Product Information

Model	RG-RAP2260(H)
Product Type	Ceiling AP

/ Hardware Specifications

Model	RG-RAP2260(H)
Wi-Fi Radio	
6 GHz Wi-Fi	No
5 GHz Wi-Fi	Wi-Fi 4 (IEEE 802.11a/n)
	Wi-Fi 5 (IEEE 802.11ac)
	Wi-Fi 6 (IEEE 802.11ax)
2.4 GHz Wi-Fi	Wi-Fi 4 (IEEE 802.11b/g/n)
	Wi-Fi 6 (IEEE 802.11ax)
Operating band	IEEE 802.11b/g/n/ax, 2.400 GHz to 2.4835 GHz IEEE 802.11a/n/ac/ax, 5.150 GHz to 5.350 GHz, 5.470 GHz to 5.725 GHz, 5.725 GHz to 5.850 GHz Note: Available bands vary with countries and regions. To use the preceding frequency bands, ensure that your country or region supports these frequency bands.
Radio design	Dual-radio 8 spatial streams

Hardware Specifications

Model	RG-RAP2260(H)
	<ul style="list-style-type: none"> • 2.4 GHz: 4 x 4, MU-MIMO • 5 GHz: 4 x 4, MU-MIMO
FEM	2.4 GHz: 4 x eFEM 5 GHz: 4 x eFEM
6 GHz channel width	No
5 GHz channel width	Auto/20/40/80/160 MHz
2.4 GHz channel width	Auto/20/40 MHz
Maximum wireless data rate	5950 Mbps
6 GHz wireless data rate	No
5 GHz wireless data rate	4803 Mbps
2.4 GHz wireless data rate	1147 Mbps
Maximum transmit power	Frequency bands and maximum Effective Isotropic Radiated Power (EIRP): Note: Country specific restrictions apply. European Union & United Kingdom: 2400–2483.5 MHz, EIRP ≤ 20 dBm 5150–5350 MHz, EIRP ≤ 23 dBm 5470–5725 MHz, EIRP ≤ 30 dBm United States: 2400–2483.5 MHz, max output power ≤ 30 dBm & EIRP ≤ 36 dBm

/ Hardware Specifications

Model	RG-RAP2260(H)
	5150–5250 MHz, max output power ≤ 30 dBm & EIRP ≤ 36 dBm
	5250–5350 MHz, max output power < 24 dBm & EIRP ≤ 30 dBm
	5470–5725 MHz, max output power < 24 dBm & EIRP ≤ 30 dBm
	5725–5850 MHz, max output power ≤ 30 dBm & EIRP ≤ 36 dBm
	Myanmar:
	2400–2483.5 MHz, EIRP ≤ 23 dBm
	5725–5825 MHz, EIRP ≤ 30 dBm
	Thailand:
	2400–2483.5 MHz, EIRP ≤ 20 dBm
	5150–5350 MHz, EIRP ≤ 23 dBm
	5470–5725 MHz, EIRP ≤ 30 dBm
	5725–5825 MHz, EIRP ≤ 30 dBm
	Indonesia:
	2400–2483.5 MHz, EIRP ≤ 27 dBm
	5150–5350 MHz, EIRP ≤ 23 dBm
	5725–5825 MHz, EIRP ≤ 23 dBm
	Egypt:
	2400–2483.5 MHz, EIRP ≤ 20 dBm

Hardware Specifications

Model	RG-RAP2260(H)
	5150–5350 MHz, EIRP $\leq$ 23 dBm Vietnam: 2400–2483.5 MHz, EIRP $\leq$ 23 dBm 5150–5350 MHz, EIRP $\leq$ 23 dBm 5470–5725 MHz, EIRP $\leq$ 30 dBm 5725–5850 MHz, EIRP $\leq$ 30 dBm
Maximum transmit power (6 GHz)	No
Maximum transmit power (5 GHz)	Combined power: 32 dBm (single-stream power: 26 dBm) Note: The transmit power varies according to regulations in different countries and regions.
Maximum transmit power (2.4 GHz)	Combined power: 32 dBm (single-stream power: 26 dBm) Note: The transmit power varies according to regulations in different countries and regions.
Coverage range	190 m ² (2045.14 square ft.) Note: The data is obtained in an ideal environment without obstruction. The signal coverage radius depends on client performance and environmental interference.
Modulation	OFDM: BPSK @ 6/9 Mbps, QPSK @ 12/18 Mbps, 16-QAM @ 24 Mbps, 64-QAM @ 48/54 Mbps DSSS: DBPSK @ 1 Mbps, DQPSK @ 2 Mbps, and CCK @ 5.5/11 Mbps

Hardware Specifications

Model	RG-RAP2260(H)
	MIMO-OFDM: BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM and 1024-QAM OFDMA
Receive sensitivity	11b: -91 dBm (1 Mbps), -88 dBm (5.5 Mbps), -85 dBm (11 Mbps) 11a/g: -89 dBm (6 Mbps), -80 dBm (24 Mbps), -76 dBm (36 Mbps), -71 dBm (54 Mbps) 11n: -83 dBm (MCS0), -65 dBm (MCS7), -83 dBm (MCS8), -65 dBm (MCS15) 11ac: 20 MHz: -83 dBm (MCS0), -57 dBm (MCS9) 11ac: 40 MHz: -79 dBm (MCS0), -57 dBm (MCS9) 11ac: 80 MHz: -76 dBm (MCS0), -51 dBm (MCS9) 11ac: 160 MHz: -76 dBm (MCS0), -50 dBm (MCS9) 11ax: 20 MHz: -85 dBm (MCS0), -58 dBm (MCS11) 11ax: 40 MHz: -82 dBm (MCS0), -54 dBm (MCS11) 11ax: 80 MHz: -79 dBm (MCS0), -52 dBm (MCS11) 11ax: 160 MHz: -76 dBm (MCS0), -49 dBm (MCS11)
Antenna	
Antenna	2.4 GHz: 4 built-in omnidirectional antennas 5 GHz: 4 built-in omnidirectional antennas
Antenna horizontal orientation	No

Hardware Specifications

Model	RG-RAP2260(H)
Antenna vertical orientation	No
Antenna gain (6 GHz)	No
Antenna gain (5 GHz)	4.00 dBi
Antenna gain (2.4 GHz)	3.00 dBi
Dimensions and Weight	
Product dimensions (W x D x H)	230 mm x 230 mm x 49.5 mm (9.06 in. x 9.06 in. x 1.95 in.) (excluding the mounting bracket)
Color	White
Weight	≤ 1.36 kg (3.00 lbs.) (without packaging materials)
Shipping weight	≤ 1.72 kg (3.79 lbs.)
Certification and Regulatory Compliance	
RoHS	Yes
Safety compliance	EN 62368-1
EMC	EN 55032
	EN 55035
	EN 61000-3-3
	EN 61000-3-2
	EN 301489-1
	EN 301489-3
	EN 301489-17

Hardware Specifications

Model	RG-RAP2260(H)
RF	EN 300 328
	EN 301 893
	EN 300 440
Certification	CE, FCC, CB, ISED, cTUVus
Port Specifications	
Number of 10/100/1000/2500BASE-T ports	2
Reset button	1
LEDs	1 x system status LED
System Specifications	
Flash memory	256 MB
RAM	512 MB DDR3
Environment and Reliability	
Operating temperature	0°C to 40°C (32°F to 104°F)
Storage temperature	−40°C to +70°C (−40°F to +158°F)
Operating humidity	5% RH to 95% RH (non-condensing)
Storage humidity	5% RH to 95% RH (non-condensing)
Mounting options	Ceiling/Wall
IP rating	No
Surge protection	Ethernet port: ±2 kV for common mode
MTBF	400,000 hours
Power Supply and Consumption	

Hardware Specifications

Model	RG-RAP2260(H)
Power supply	<ul style="list-style-type: none">• DC power adapter• PoE+/PoE++ <p>Note: If both the DC power adapter and PoE+/PoE++ are available for power supply, the DC power adapter is preferred.</p>
Local power supply	Yes, one DC power connector (48 V, 1 A)
Dimensions of the DC connector	Outer diameter: 5.5 mm (0.22 in.) Inner diameter: 2.1 mm (0.08 in.) Depth: 10 mm (0.39 in.)
PoE In standard	<ul style="list-style-type: none">• IEEE 802.3at (PoE+) <p>Note: Radio transmission and reception is limited to 2T2R at 2.4 GHz and 5 GHz.</p> <ul style="list-style-type: none">• IEEE 802.3bt (PoE++)
PoE budget	No
Maximum power consumption	40 W

Software Specifications

Model	RG-RAP2260(H)
WLAN	
Maximum number of associated wireless clients	64 (2.4 GHz) 512 (5 GHz) 512 (2.4 GHz and 5 GHz enabled)
Recommended number of associated wireless clients	<ul style="list-style-type: none">● Support for IEEE 802.11ax and 160 MHz: 16 (2.4 GHz) 114 (5 GHz) 130 (2.4 GHz and 5 GHz enabled)● Support for IEEE 802.11ax and 80 MHz: 16 (2.4 GHz) 104 (5 GHz) 120 (2.4 GHz and 5 GHz enabled)● Support for IEEE 802.11ac: 16 (2.4 GHz) 64 (5 GHz) 80 (2.4 GHz and 5 GHz enabled)
Maximum number of SSIDs	8
Radio-based client limiting	Yes
Layer 2 isolation	Yes
OFDMA	Yes
WMM	Yes

Software Specifications

Model	RG-RAP2260(H)
DFS	Yes
MLO	No
4K-QAM	No
Different SSIDs for the same VLAN	Yes
Enabling/Disabling MLO	No
AP load balancing	Yes
Beamforming	Yes
802.11k/v roaming	Yes
Fast transition (802.11r)	Yes
Layer 2 roaming	Yes
Layer 3 roaming	Yes
AI roaming	Yes
Co-channel roaming	Yes
Roaming sniffing	No
Configurable antenna	No
PSK authentication	Yes
Static allowlist	Yes
Adjusting the transmit power for beacon and probe frames	Yes
Encryption mode (WPA-PSK, WPA2-PSK, WPA/WPA2-PSK)	Yes

Software Specifications

Model	RG-RAP2260(H)
OWE (Enhanced Open)	Yes
WPA3-SAE	
WPA2-PSK/WPA3-SAE	
Number of blocklists and allowlists based on MAC addresses (single SSID)	256
Number of global blocklists/allowlists	256
Mesh management	Yes
AP Mesh	Yes
AP portal authentication	Yes
Maximum number of devices that can be managed	300
One-Click Network Optimization	Yes
Static blocklist	Yes
Interface	
IPTV transparent transmission	No
Authentication	
802.1X authentication	Yes
Dynamic VLAN assignment	Yes

Software Specifications

Model	RG-RAP2260(H)
IPv4 Ruijie RG-OCE Identity Manager authentication scheme	Yes
Linkufi authentication	Yes
Network Management and Monitoring	
Wireless repeater mode	Yes
Web login information	Single-device login address: 10.44.77.254 Network-wide login address: 10.44.77.253 Default password: admin
Network-wide configuration and management	Yes
Ruijie Reyee App management	Yes
eWeb management	Yes
Ruijie Cloud management	Yes
SNMP	Yes
Configuration synchronization among the app, eWeb, and Ruijie Cloud	Yes
Displaying device information on Ruijie Cloud	Yes
Ethernet Switching	
IEEE 802.1Q VLAN	Yes

Software Specifications

Model	RG-RAP2260(H)
VLAN expansion	Yes
Enabling/Disabling an interface	Yes
Interface rate	10/100/1000/2500 Mbps auto-negotiation
Interface mode (half-duplex/full-duplex switching)	Yes
Ethernet Interface	
PPPoE clients	Yes
Basic Configurations	
AP mode	Yes
Routing mode	Yes
Internet access mode	Static IP address Static IPv6 address Dynamic IP address Dynamic IPv6 address PPPoE
Multicast	
IGMP snooping (wireless-to-wireless)	Yes
IGMP snooping (wired-to-wireless)	Yes
IGMP snooping (wired-to-wired)	No
IP Service	
ARP binding	Yes

Software Specifications

Model	RG-RAP2260(H)
IPv4 ping	Yes
IPv6 ping	Yes
Traceroute	Yes
Static/Dynamic NAT	Yes
DHCP server	Yes
IPv6	Yes

Package Contents

Model	RG-RAP2260(H)
Package Contents	
Package Contents	1 x AP
	1 x Mounting bracket
	4 x Cross pan head screws (ST4.2 x 20 mm)
	4 x Plastic expansion anchors (ϕ 9 x 25.4 mm)
	1 x User Manual
	1 x Warranty Card
	1 x Key to security lock
Accessories	
Power adapter	No

Ruijie | ReYee

 **R**edefine **y**our **e**asy network



Ruijie Networks Co., Ltd.

Official Website: <https://Reyee.Ruijie.com>