Product data sheet
Characteristics

SBP1500RMI
APC SERVICE BYPASS PDU, 230V 10AMP W/ (6) IEC C13



Main

Main Input Voltage	230 V
Product or component type	Bypass kit
Output voltage	230 V
Input Connection Type	IEC 60320 C14
Number of rack unit	2U
Cable length	2.0 M
Number of cables	1
Provided equipment	User manual Rack mounting brackets
Range of product	Maintenance Bypass Panels

Physical

Colour	Black
Height	89 Mm
Width	432 Mm
Depth	76 Mm
Net weight	2 Kg
Mounting location	Front
Mounting preference	No preference
Mounting mode	Rack-mounted

Input

Network frequency	50/60 Hz
Permissible voltage	220…240 V
Max line current	10 A
Input current limits	10 A
Load capacity	1500 VA
Power factor	0…1

Output

Max current draw	10 A
Number of power socket outlets	6 IEC 60320 C13 1 IEC Jumpers
Number of power socket outlets	6
Protection type	Circuit breaker
Power cable length	1.2 M
Efficiency	99 %

Conformance

Product certifications	VDE
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

Environmental

Ambient air temperature for operation	0…40 °C
Relative humidity	0…95 %
Operating altitude	0...15000 ft
Ambient air temperature for storage	-15…45 °C
Storage Relative Humidity	0…95 %
Storage altitude	0…15240 M

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	15.100 Cm
Package 1 Width	46.300 Cm
Package 1 Length	29.500 Cm
Package 1 Weight	3.490 Kg
Unit Type of Package 2	PAM
Number of Units in Package 2	56
Package 2 Height	111.000 Cm
Package 2 Width	120.000 Cm
Package 2 Length	100.000 Cm
Package 2 Weight	195.440 Kg

Offer Sustainability

Mercury free	Yes
Sustainable packaging	No
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	7a19864b-8bf5-40ac-85e8-7678b0910185
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant By Exemption
Take-back	Yes
WEEE Label	The product must be disposed on European Union markets following specific waste collection and

Contractual warranty

Warranty (in months)	24

Product Life Status : Commercialised