Product data sheet
Characteristics

SBP3000RMI
APC SERVICE BYPASS PDU, 230V 16AMP W/ (6) IEC C13 AND (1) C19



Main

Main Input Voltage	230 V
Product or component type	Bypass kit
Output voltage	230 V
Input Connection Type	IEC 60320 C20
Number of rack unit	2U
Cable length	2.5 M
Number of cables	1
Provided equipment	User manual Rack mounting brackets
Range of product	Maintenance Bypass Panels

Physical

Colour	Black
Height	89 Mm
Width	432 Mm
Depth	76 Mm
Net weight	2.09 Kg
Mounting location	Front
Mounting preference	No preference
Mounting mode	Rack-mounted

Input

Network frequency	50/60 Hz
Permissible voltage	220…240 V
Max line current	16 A
Input current limits	16 A
Load capacity	3000 VA
Power factor	0…1

Output

Max current draw	16 A
Number of power socket outlets	6 IEC 60320 C13 1 IEC Jumpers 1 IEC 60320 C19
Number of power socket outlets	7
Protection type	Circuit breaker
Power cable length	1.00 M
Efficiency	99 %

Conformance

Product certifications	VDE
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

Environmental

Ambient air temperature for operation	0…40 °C
Relative humidity	0…95 %
Operating altitude	0...15000 ft
Ambient air temperature for storage	-15…45 °C
Storage Relative Humidity	0…95 %
Storage altitude	0…15240 M

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	15.1 Cm
Package 1 Width	29.5 Cm
Package 1 Length	46.3 Cm
Package 1 Weight	3.91 Kg

Offer Sustainability

REACh free of SVHC	Yes
Toxic heavy metal free	Yes
Mercury free	Yes
Sustainable packaging	No
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	7a19864b-8bf5-40ac-85e8-7678b0910185
REACh Regulation	Free of Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant
Take-back	Yes
WEEE Label	The product must be disposed on European Union markets following specific waste collection and

Contractual warranty

Warranty (in months)	24

Product Life Status : Commercialised