Product data sheet
Characteristics

SRT2200RMXLI-NC
APC Smart-UPS On-Line, 2200VA, Rackmount 2U, 230V, 8x C13+2x C19 IEC outlets, Network Card, Extended runtime, W/ rail kit



Overview

Presentation	High density, double-conversion on-line power protection with scalable runtime.

Main

Main Input Voltage	230 V AC 1 phase
Input voltage	220 V 240 V
Input Connection Type	BS 1363 British IEC 60320 C20 CEE 7/7
Input voltage limits	100...275 V adjustable (half load)
Network frequency	40...70 Hz auto-sensing
Output voltage	230 V AC 1 phase
Output voltage	220 V 240 V
Rated power in W	1980 W
Rated power in VA	2200 VA
Output connection type	8 IEC 60320 2 IEC Jumpers 2 IEC 60320
Bypass type	Built-in bypass
Crest factor	3 : 1
Harmonic distortion	Less than 2 %
Maximum configurable power in VA	2200 VA
Maximum configurable power in W	1980 W
UPS type	On-Line
Wave type	Sine wave
Output frequency	50/60 Hz +/- 3 Hz sync to mains

Complementary

Battery type	Lead-acid internal included
Emergency power off	Yes
Free slots	1
Preinstalled device	Network management card 3 with environmental monitoring
Alarm	Audible and visible alarms : prioritized by severity

UPS connectivity	Serial port USB port Pre-installed network management card 3
Surge energy rate	340 J
Number of rack unit	2U
Cable length	2.4 M
Number of cables	1
Colour	Black
Height	85 Mm
Width	432 Mm
Depth	584 Mm
Net weight	25 Kg
Mounting location	Front
Mounting preference	Lower
Mounting mode	Rack-mounted
Two post mountable	0
USB compatible	Yes
Mounting position	Horizontal
Mounting mode	Rack-mounted with kit sold separately
Provided equipment	CD with software Country-specific detachable power cord Documentation CD Installation guide Network management card Rack mounting hardware Rack mounting brackets Rack mounting support rails USB cable Warranty card
Number of power module	1400
Number of power module filled slots	0
Number of power module free slots	0
Additional specification	High density
Redundant	No
Range of product	Smart-UPS On-Line
Product or component type	Uninterruptible power supply (UPS)

Environment

Product certifications	CE[RETURN]EAC[RETURN]RCM[RETURN]VDE[RETURN]UK PSTI
Marking	CE Mark
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
Ambient air temperature for operation	0…40 °C
Ambient air temperature for storage	-20…50 °C
Storage altitude	0…15240 M
IP degree of protection	IP20
Relative humidity	0…95 % non-condensing
Storage Relative Humidity	0…95 % non-condensing
Acoustic level	55 dBA
Heat dissipation	535 Btu/H
Operating altitude	0...10000 ft

Batteries & Runtime

Battery type	Lead-acid battery
Battery voltage	72 V
Extended runtime	1
Number of battery filled slots	1
Number of battery free slots	0
Battery recharge time	3 H

Number of battery replacement quantity	1
Battery life	3…5 Year(S)
Battery charger power	122 W rated

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	24.5 Cm
Package 1 Width	60 Cm
Package 1 Length	81.5 Cm
Package 1 Weight	33.105 Kg
Unit Type of Package 2	P12
Number of Units in Package 2	3
Package 2 Height	90.000 Cm
Package 2 Width	80.000 Cm
Package 2 Length	120.000 Cm
Package 2 Weight	111.315 Kg

Offer Sustainability

Recyclability potential, in %	65
Total lifecycle Carbon footprint	6 765 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	399.46552
Carbon footprint of the manufacturing phase [A1 to A3]	399 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	4.4220054
Carbon footprint of the distribution phase [A4]	4 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	6357.1587830392
Carbon footprint of the use phase [B2, B3, B4, B6]	6 357 kg CO2 eq.
Lead free	Yes
Mercury free	Yes
Sustainable packaging	No
Carbon footprint of the end-of-life phase [C1 to C4]	3.8964096
Carbon footprint of the end-of-life phase [C1 to C4]	4 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Total lifecycle Carbon footprint	6765
Average percentage of recycled plastic content	15 %
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	4282bd22-a353-4f82-bb5c-97bbd7f1d1e9
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant By Exemption
Removable battery	User replaceable
Take-back	Yes
WEEE Label	The product must be disposed on European Union markets following specific waste collection a

Contractual warranty

Warranty (in months)	24 Battery|36 UPS

Product Life Status : Commercialised