Product data sheet
Characteristics

SRT5KXLI
APC Smart-UPS On-Line, 5kVA, Tower, 230V, 6x C13+4x C19 IEC outlets, Network Card +SmartSlot, Extended runtime, W/O rail kit



Overview

Presentation	High density, double-conversion on-line power protection with scalable runtime.

Main

Main Input Voltage	230 V AC 1 phase
Input voltage	220 V 240 V
Input voltage limits	100...275 V adjustable (half load)
Number of input connectors	1 hard wire 3-wire (1P + N + E)
Network frequency	40...70 Hz auto-sensing
Output voltage	230 V 1 phase
Output voltage	220 V 240 V
Rated power in W	4500 W
Rated power in VA	5000 VA
Output connection type	6 IEC 60320 2 IEC Jumpers 4 IEC 60320
Bypass type	Internal bypass (automatic and manual)
Crest factor	3 : 1
Harmonic distortion	Less than 2 %
Maximum configurable power in VA	5000 VA
Maximum configurable power in W	4500 W
UPS type	On-Line
Wave type	Sine wave
Output frequency	50/60 Hz +/- 3 Hz sync to mains

Complementary

Battery type	Lead-acid internal included
Emergency power off	Yes
Free slots	1
Preinstalled device	Network management card 3 with environmental monitoring
Alarm	Audible and visible alarms : prioritized by severity

UPS connectivity	Serial port USB port Pre-installed network management card 3
Surge energy rate	480 J
Colour	Black
Height	432 Mm
Width	130 Mm
Depth	719.4 Mm
Net weight	54.43 Kg
Mounting location	Front
Mounting preference	No preference
Mounting mode	Rack-mounted with kit
Two post mountable	0
USB compatible	Yes
Mounting mode	Rack-mounted with included kit
Provided equipment	CD with software Communication cable Documentation CD Installation guide Removable support feet Temperature probe USB cable Warranty card Web/SNMP management card
Number of power module filled slots	0
Number of power module free slots	0
Additional specification	High density
Redundant	No
Range of product	Smart-UPS On-Line
Product or component type	Uninterruptible power supply (UPS)

Environment

Product certifications	CE[RETURN]EAC[RETURN]IRAM[RETURN]RCM[RETURN]VDE
Marking	CE Mark
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
Ambient air temperature for operation	0…40 °C
Ambient air temperature for storage	-15…45 °C
Storage altitude	0…15240 M
IP degree of protection	IP20
Relative humidity	0…95 % non-condensing
Storage Relative Humidity	0…95 % non-condensing
Acoustic level	55 dBA
Heat dissipation	931 Btu/H
Operating altitude	0...10000 ft

Batteries & Runtime

Battery type	Lead-acid battery
Battery voltage	192 V
Extended runtime	1
Number of battery filled slots	2
Number of battery free slots	0
Battery recharge time	1.5 H
Number of battery replacement quantity	1
Battery life	3…5 Year(S)
Battery charger power	560 W rated

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	33.000 Cm
Package 1 Width	96.000 Cm
Package 1 Length	61.000 Cm
Package 1 Weight	63.599 Kg

Offer Sustainability

Recyclability potential, in %	65
Total lifecycle Carbon footprint	11 178 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	798.8565886154
Carbon footprint of the manufacturing phase [A1 to A3]	799 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	8.8431866377
Carbon footprint of the distribution phase [A4]	9 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	10362.7972288187
Carbon footprint of the use phase [B2, B3, B4, B6]	10 363 kg CO2 eq.
Sustainable packaging	No
Carbon footprint of the end-of-life phase [C1 to C4]	7.7920929969
Carbon footprint of the end-of-life phase [C1 to C4]	8 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Total lifecycle Carbon footprint	11178
Average percentage of recycled plastic content	15 %
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	409c68a1-39a6-4e5f-b080-12befe783ad8
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant By Exemption
Removable battery	User replaceable
Take-back	Yes
WEEE Label	The product must be disposed on European Union markets following specific waste collection a

Contractual warranty

Warranty (in months)	36 UPS|24 Battery

Product Life Status : Commercialised